

# Installer Series MM Test Kit

SKU: IS-KIT-M

Multimode Fiber Test Kit

## Overview

Many fiber optic network bids and Requests For Quote (RFQ) are citing cabling standards to specify the set of guidelines (such as fiber length) that the network installer must follow during the network installation. Adherence to such standards is meant to ensure the quality of the installation and guarantee that the network will perform as it was designed.

The process of testing a network installation to ensure its adherence to specified standards is called certification, and often requires hard-copy documentation as proof of adherence to standards.

The **Installer Series MM Test Kit** contains the tools necessary for certifying multimode fiber optic links against a myriad of popular cabling standards, including two user-customizable standards.

The **Micro OWL 2 optical power meter** is multimode and singlemode ready, and contains a user-friendly Fiber Link Wizard that performs link budget calculation, and sets a reference value using the characteristics of the link. This reference is the PASS/FAIL threshold and is calculated against the chosen standard. Up to 1000 fiber runs may be stored, and downloaded to a PC for report generation using our OWL Reporter software. Its universal port allows connections to ST, SC, and FC, and also includes a 1.25mm universal port for connection to LC, MU, and other SFF connectors.

The **WaveSource MM** multimode LED source contains a single-port, dual-wavelength output (850nm / 1300nm), which is temperature-stabilized for accurate measurements, and is housed in a SC connector port.

## Kit Contents

|                      |  |
|----------------------|--|
| <b>Power Meter:</b>  | Micro OWL 2  |
| <b>Light Source:</b> | WaveSource MM  |
| <b>Accessories:</b>  | OWL Reporter software<br>Product manuals<br>Download cable<br>9-volt batteries<br>NIST certificate<br>Carrying case<br>Protective rubber boots |



## Features

Fiber optic link certification of multimode fiber links at 850nm and 1300nm against a myriad of cabling standards, including two user-customizable standards

Data storage for up to 1000 data points including run labels, fiber type, and link information including link name, date, reference power values, fiber length, and number of splices and interconnects

Built-in loss wizard for calculation of maximum allowable loss values (link budget)

USB interface for continuous data logging, report printing, or data downloading

OWL Reporter software for printing formatted fiber certification reports

Absolute or relative mode for giving you instant pass/fail results

Selectively view, delete or resample data points

## Supported Cabling Standards

EIA/TIA 568  
ISO/IEC 11801  
10-Gig Ethernet  
+000Base-SX/LX  
100Base-FX  
10Base-FB/FL  
FDDI  
ATM-155/622  
Fibre Channel  
Token Ring

Also supports 2 user-customizable standards

Product manuals come in PDF format on CD. Adobe Acrobat Reader™ is required to view these documents.

Patch cables are available for an additional charge. Contact OWL for more information.



ASSEMBLED IN USA  
N.I.S.T. Traceable



**o.w.l.** MANUFACTURER OF QUALITY OPTICAL FIBER TEST EQUIPMENT  
OPTICAL WAVELENGTH LABORATORIES™



Optical Wavelength Laboratories (OWL)  
N9623 West US Hwy 12  
Whitewater, WI 53190  
Phone (262)473-0643 Fax: (262)473-8737  
<http://owl-inc.com>