

Silicon ZOOM II / Dual OWL 850 Test Kit

SKU: KIT-Z2S-D285st (ST connector option)
SKU: KIT-Z2S-D285sc (SC connector option)

Multimode Fiber Test Kit

Overview

The **Silicon ZOOM II / Dual OWL 850 Test Kit** is ideal for LAN managers and installers who need to do simple attenuation tests on their multimode networks.

The **Silicon ZOOM II (Zeroed Output Optical Meter)** is an economical fiber optic power meter designed to provide accurate testing of multimode fiber cables at 850nm wavelength. The 4-digit 7-segment LCD display shows power readings with a resolution of 0.01dB, power units in dBm, dB, or uW, and battery power level. The **Silicon ZOOM II** comes configured with a 2.5mm universal port for connection to SC, ST, and other connector types that have a 2.5mm ferrule.

The **Dual OWL 850** is an 850nm NIST traceable multimode light source. Its 850nm output is temperature-stabilized for accurate measurements. The **Dual OWL 850** has two connector options: ST or SC.



Features

Economical option for quick attenuation and loss testing of multimode networks at 850nm

Easy-to-read 4-digit 7-segment LCD display

Store reference values for calibrated wavelengths

Intuitive 2-button interface on both units

On-screen wavelength, measurement units, and low battery indicator

NIST traceable

Kit Contents

- Power Meter:** Silicon ZOOM II
- Light Source:** Dual OWL 850
- Accessories:** Product manuals
9-volt batteries
NIST certificate
Carrying case
Protective rubber boots



MADE IN USA

N.I.S.T. Traceable

Product manuals come in PDF format on CD. Adobe Acrobat Reader™ is required to view these documents.

Carrying cases and patch cables are available for an additional charge. Call 262-473-0643 for more information.



o.w.l. MANUFACTURER OF QUALITY OPTICAL FIBER TEST EQUIPMENT
OPTICAL WAVELENGTH LABORATORIES™



Optical Wavelength Laboratories (OWL)
N9623 West US Hwy 12
Whitewater, WI 53190
Phone (262)473-0643 Fax: (262)473-8737
<http://owl-inc.com>

Silicon ZOOM II / Dual OWL 850 Test Kit

Multimode Fiber Test Kit

SKU: KIT-Z2S-D285st (ST connector option)
SKU: KIT-Z2S-D285sc (SC connector option)

Specifications

Silicon ZOOM II Optical Power Meter

Detector	Si 1mm
NIST Traceable	850nm
Wavelengths	
Additional Factory	650nm, 980nm
Calibrated Wavelengths	
Measurement Range	+5 to -60 dBm
Accuracy ¹	±0.15 dB
Linearity ¹	±0.20 dB
Resolution	0.01 dBm
Battery Life	up to 250 hours
Operating Temperature	0 to 55°C
NIST Traceable	Yes
Battery Capacity Display	Yes
Connector	2.5mm universal port
Width	2.75"
Height	4.94"
Depth	1.28"
Weight	154g

1: Over range of 0 to -45 dBm

Conforms to the Harmonized European Standards EN 61326-1 and EN 61010-1.


Dual OWL 850 Multimode Light Source

Launch Method	LED
Connector	ST or SC
Center Wavelength	850 ±20nm
Spectral Width (FWHM)	35 nm
Output Power	-20.0 dBm
Initial Accuracy	0.1 dB
Fiber Type	multimode
Battery Life	40 hrs.
Battery Capacity Display	Yes
Operating Temperature	0 to 55° C
Storage Temperature	0 to 75° C
Width	2.75"
Height	4.94"
Depth	1.28"
Weight	154g

Conforms to the Harmonized European Standards EN 61326-1 and EN 61010-1.



o.w.l. MANUFACTURER OF QUALITY OPTICAL FIBER TEST EQUIPMENT
OPTICAL WAVELENGTH LABORATORIES™



Optical Wavelength Laboratories (OWL)
N9623 West US Hwy 12
Whitewater, WI 53190
Phone (262)473-0643 Fax: (262)473-8737
<http://owl-inc.com>