## Optical Wavelength Laboratories Presents



# **POCKET SINGLEMODE**



- Compact size
  - Color LCD display
    - Breakthrough pricing

#### **OWLTrek OTDR**

### **OWL - The WISE choice in fiber test!**

#### Small, pocket-sized OTDR does same job as larger, more expensive OTDRs, for a fraction of the cost


With an unbeatable combination of a small pocket-sized form factor, a large high-resolution 2.8" color LCD display, and some of the lowest pricing in the industry, the OWLTrek OTDR from OWL is the WISE choice for cost-conscious buyers who only need to perform basic troubleshooting or restoration tasks on singlemode optical fiber networks. All this from an OTDR that really is pocket-sized and fair priced, yet having comparable features and specifications to other OTDRs in its class.


**Affordability.** In a time when it is becoming increasingly difficult to justify equipping an entire technical staff with high-end equipment, companies are even more cost-conscious than before. Outfit a majority of the installation/repair trucks with OWLTrek OTDRs, and set aside a few high-end "expert" vehicles for high-priority roll-outs.

**Usability.** The OWLTrek OTDR may be pocket-sized, but the large 2.8" high-resolution color LCD display can show even the longest traces with ease. And, for greater viewing flexibility and trace detail, OWL has implemented state-of-the-art MEMS technology which "flips" the high-resolution color LCD display between portrait and landscape mode automatically. In landscape mode, a wider viewing area means greater viewing detail.

**Automatic Event Location.** Automatic event location is an advanced feature normally found only in expensive, high-end OTDRs. The OWLTrek OTDR now brings this feature to the entry-level OTDR market. While in event location mode, the OWLTrek OTDR marks events on the trace, has an event table showing the location, type, reflectance level, and loss of each event, and auto-zooms to the selected event.

Call OWL at 262-473-0643 for more information about this new and exciting development in OTDR testing, and discover why OWL is the wise choice in fiber test equipment!





		Optical Specifications	
Model #:	WTO-S13	WTO-S15	WTO-S35
Output Wavelength:	1310nm	1550nm	1310/1550nm
Fiber Type:	Singlemode		
Dynamic Range (SNR=1)2:	25 dB	23 dB	25/23 dB
Distance Range⁵:	80 miles (128 kilometers)		
Event Dead Zone <sup>3</sup> :	2 meters (typical)		
Attenuation Dead Zone⁴:	7 meters (typical)		
Maximum Data Points:	64000		
Data Point Spacing:	Up to 64km: 1 meter // Over 64km: 2 meters		
Pulse Width:	1, 2, 5, 10, 20, 50, 100, 200, 500, 1000 meters		
Index of Refraction:	1.4000 to 1.6000		
Distance Accuracy:	Up to 64km: 1 + (distance in meters/10000) // Over 64km: 2 + (distance in meters/10000)		
Number of Stored Traces:	Maximum trace dist	ance: up to 200 // Minimum tr	ace distance: 3000+

1: All price shown are in US Dollars (USD). List price is shown for US customers only. Prices outside
the US may vary based on individual countries' import duties and taxes, currency conversion, and
other value added charges.

<sup>2:</sup> Using maximum pulse width

width neter pulse width	o		ries '
	The Wise	OWL	est est
ASSEMBLED IN US	A .	Choice in Optical	S. C.

General Specifications				
Display Type:	High-resolution Color LCD			
Display Size:	2.8" diagonal			
Battery Type:	Lithium Polymer			
Battery Life:	up to 20 hours normal usage			
Dimensions:	2.87" x 4.42" x 1.25"			
Weight:	10 ounces (284 g)			
Visual Fault	Locator Specifications			
Output Wavelength:	650nm			
Output Power:	1 mW			
Operating Mode:	CW / Flash			

Ordering Information					
Model #:	List Price1:	Sale Price <sup>1</sup> :			
WTO-S13	1995.00	1595.00			
WTO-S15	1995.00	1595.00			
WTO-S35	2995.00	2495.00			

For a limited time, OWLTrek OTDRs are being sold at a promotional discount.

Contact OWL at 262-473-0643 to take advantage of this promotional price.

Optical Wavelength Laboratories
Phone: 262-473-0643 · Internet: OWL-INC.COM

<sup>3:</sup> Width measured 1.5dB down on each side of a reflective event using 1 meter pulse width

<sup>4:</sup> Distance from event beginning to within 0.5dB where backscatter resumes using 1 meter pulse width

<sup>5:</sup> Out to furthest reflective event