

Micro OWL 2 FTTH Test Kit

SKU: KIT-M2-FTTHst
SKU: KIT-M2-FTTHsc

Singlemode Fiber Test Kit

Overview

Many fiber optic network bids and Requests For Quote (RFQ) are citing cabling standards to specify the set of guidelines (such as fiber length) that the network installer must follow during the network installation. Adherence to such standards is meant to ensure the quality of the installation and guarantee that the network will perform as it was designed.

The process of testing a network installation to ensure its adherence to specified standards is called certification, and often requires hard-copy documentation as proof of adherence to standards.

The **Micro OWL 2 FTTH Test Kit** contains the tools necessary for measuring optical loss in fiber optic networks using the ITU G.983.3, the standard used for Fiber To The Home (FTTH) networks.

The **Micro OWL 2 optical power meter** is multimode and singlemode ready, and contains a user-friendly Fiber Link Wizard that performs link budget calculation and sets a reference value using the characteristics of the link. This reference is the PASS/FAIL threshold and is calculated against the chosen standard. Up to 1000 fiber runs may be stored, then downloaded to a PC for report generation using our OWL Reporter software.

It also includes intelligent automated testing functions, such as automatic dual-wavelength storage and auto-wavelength recognition, which reduce testing time and human error.

The **WaveSource FTTH fiber optic light source** contains the three wavelengths (1310, 1490, and 1550 nm) required by the ITU G.983.3 FTTH standard in a single unit, designed for accurate testing and certification of FTTH networks. Its outputs are temperature-stabilized for accurate measurements.

The **WaveSource FTTH** has a built-in auto-wavelength switching protocol designed to synchronize the wavelength of the **Micro OWL 2** with the current output wavelength.

Three connector options are available (ST, SC, and FC).

Kit Contents

Power Meter:	Micro OWL 2	Light Source:	WaveSource FTTH
Accessories:	OWL Reporter software NIST certificate	Product manuals Carrying case	Download cable 9-volt batteries Protective rubber boots



ASSEMBLED IN USA
N.I.S.T. Traceable

Features

- Optical loss and certification of FTTH fiber links at 1310, 1490, and 1550nm
- Auto-wavelength recognition and automatic data storage reduce testing time and human error
- Optional integrated fiber optic length tester for accurate link length measurements
- Data storage for up to 1000 data points including run labels, fiber type, and link information including link name, date, reference power values, fiber length, and number of splices and interconnects
- Built-in FTTH loss parameters for on-screen PASS/FAIL readings
- USB interface for continuous data logging, report printing, or data downloading
- OWL Reporter software for printing formatted fiber certification reports
- Absolute or relative mode for giving you instant pass/fail results
- Selectively view, delete or resample data points

Additional Supported Cabling Standards:

EIA/TIA 568-B/C	ISO/IEC 11801	10-Gigabit Ethernet
1000Base-SX	1000Base-LX	100Base-FX
10Base-FB	10Base-FL	FDDI
ATM-155	ATM-622	Fibre Channel
Token Ring		


Also supports 2 user-definable standards

Additional Power Meter Calibrated Wavelengths:

850nm 980nm 1300nm 1625nm

Product manuals come in PDF format on CD. Adobe Acrobat Reader™ is required to view these documents.

Patch cables are available for an additional charge. Contact OWL for more information.



Micro OWL 2 FTTH Test Kit

SKU: KIT-M2-FTTHst
SKU: KIT-M2-FTTHsc

Singlemode Fiber Test Kit

Specifications

Micro OWL 2 Optical Power Meter

Detector Type	InGaAs
Calibrated Wavelengths	850, 980, 1300, 1310, 1490, 1550, 1625nm
Measurement Range	+5 to -70 dBm
Accuracy	±0.15 dB
Resolution	0.01 dB
Battery Life	up to 100 hours (9V)
Connector Type	2.5/1.25mm Universal
Data Storage Points	up to 1000
Download Data Points	OWL Reporter Software
Power Units Displayed	dBm, dB, µW
Battery Capacity Display	Yes
Backlight	Yes
NIST Traceable	Yes
Auto-shutdown	Yes
Operating Temperature	-10 to 55 C
Storage Temperature	-30 to 70 C
Width	3.48"
Height	6.48"
Depth	1.1"
Weight	373g (12 oz.)

Conforms to the Harmonized European Standards EN 61326-1 and EN 61010-1.


WaveSource FTTH Fiber Optic Light Source

Launch Method (singlemode)	FP Laser
Connector	ST, SC, or FC
Center Wavelength (1310nm)	1310 ±30nm
Center Wavelength (1490nm)	1490 ±10nm
Center Wavelength (1550nm)	1550 ±30nm
Spectral Width (FWHM; 1310nm)	2nm
Spectral Width (FWHM; 1490nm)	2nm
Spectral Width (FWHM; 1550nm)	2nm
Output Power (all wavelengths)	-10.0 dBm
Initial Accuracy	0.1 dB
Output Modes	Continuous Wave Modulated
Battery Life	up to 30 hrs.
Battery Type	9V alkaline
Battery Capacity Display	Yes
Operating Temperature	0 to 55° C
Storage Temperature	0 to 75° C
Width	2.75"
Height	4.94"
Depth	1.28"
Weight	154g

Conforms to the Harmonized European Standards EN 61326-1 and EN 61010-1.



o.w.l. MANUFACTURER OF QUALITY OPTICAL FIBER TEST EQUIPMENT
OPTICAL WAVELENGTH LABORATORIES™



Optical Wavelength Laboratories (OWL)
N9623 West US Hwy 12
Whitewater, WI 53190
Phone (262)473-0643 Fax: (262)473-8737
<http://owl-inc.com>