WaveTester HP / WaveSource 1310/1550 Test Kit

SKU: KIT-WTC-WSSDxx (see connector options below)

Overview

Many fiber optic network bids and Requests For Quote (RFQ) are citing cabling standards to specify the set of guidelines (such as fiber length) that the network installer must follow during the network installation. Adherence to such standards is meant to ensure the quality of the installation and quarantee that the network will perform as it was designed.

The process of testing a network installation to ensure its adherence to specified standards is called certification, and often requires hardcopy documentation as proof of adherence to standards.

The WaveTester HP/WaveSource 1310/1550 Test Kit contains the tools necessary for certifying fiber optic links against a myriad of popular cabling standards in singlemode networks.

The WaveTester HP optical power meter is multimode and singlemode ready, and can store reference values for all wavelengths used for optical loss measurements. Up to 200 fiber runs may be stored, and serially downloaded to a PC for report generation using our OWL Reporter software.

The WaveSource 1310/1550 singlemode light source has dual wavelength outputs (1310 nm & 1550 nm) that are temperaturestabilized for accurate measurements. Two connector options are available (ST or SC).



Features

Certification of singlemode fiber links at 1310 nm and 1550 nm

Auto-test functions store references and data points automatically

Data storage for up to 200 data points

USB interface for continuous data logging, report printing, or data

Singlemode Fiber Certification Test Kit

OWL Reporter software for printing formatted fiber certification

Measurement modes include absolute (for optical power) or relative (for optical loss)

Selectively view, delete or resample data points

Supported Cabling Standards:

EIA/TIA 568-B ISO/IEC 11801 10-Gigabit Ethernet

100Base-FX 1000Base-SX 1000Base-LX

10Base-FB 10Base-FL FDDI

ATM-155 ATM-622 Fibre Channel

Token Ring

Additional Power Meter Calibrated Wavelengths:

850nm 1300nm

Kit Contents

Power Meter: WaveTester HP

Light Source: WaveSource 1310/1550 Accessories: **OWL** Reporter software

> Product manuals Download cable 9-volt batteries NIST certificate Carrying case

Protective rubber boots Carrying Straps



Product manuals come in PDF format on CD. Adobe Acrobat Reader[™] is required to view these documents.

Patch cables are available for an additional charge. Contact OWL for more information.



0.W.L MANUFACTURER OF QUALITY OPTICAL FIBER TEST EQUIPMENT OPTICAL WAVELENGTH LABORATORIES™

Optical Wavelength Laboratories (OWL) N9623 West US Hwv 12 Whitewater, WI 53190 Phone (262)473-0643 Fax: (262)473-8737 http://owl-inc.com

WaveTester HP / WaveSource 1310/1550 Test Kit

SKU: KIT-WTC-WSSDxx (see connector options below)

Specifications

Specifications		
WaveTester HP Optical Power Meter		
Detector Type	InGaAs	
NIST Traceable Wavelengths	850 nm, 1300nm, 1310nm 1550 nm	
Measurement Range	+25 to -40 dBm	
Accuracy	±0.15 dB	
Resolution	0.01 dB	
Connector Type	2.5mm Universal	
Data Storage Points	up to 200	
Download Data Points	OWL Reporter Software	
Power Units Displayed	dBm, dB, μW	
Battery Life	250 hrs. (9v alkaline)	
Battery Capacity Display Yes		

Battery Capacity Display Yes
Backlight Yes
NIST Traceable Yes
Auto-shutdown Yes
Operating Temperature -10 to 55 C

 Storage Temperature
 -30 to 70 C

 Width
 2.75"

 Height
 4.94"

 Depth
 1.28"

 Weight
 154g

Conforms to the Harmonized European Standards EN 61326-1 and EN 61010-1.

WaveSource 1310/1550 Singlemode Laser Source		
Launch Method	FP Laser	
Connector	ST or SC	
Center Wavelength (1310 nm)	1310 ±30 nm	
Center Wavelength (1550 nm)	1550 ±30 nm	
Spectral Width (FWHM; 1310 / 1550 nm)	2 nm	
Output Power	-10.0 dBm	
Initial Accuracy	0.1 dB	
Fiber Type	singlemode	
Battery Capacity Display	Yes	
Operating Temperature	-20 to +70° C	
Storage Temperature	-40 to +85° C	
Width	2.75"	
Height	4.94"	
Depth	1.28"	
Weight	154g	
Conforms to the Harmonized European Standards EN 61326-1 and EN 61010-1.		