

# ZOOM 2C / Laser OWL Test Kit

SKU: KIT-Z2C-L2xx (see connector options below)

Singlemode Fiber Test Kit

## Overview

The **ZOOM 2C / Laser OWL Test Kit** is ideal for LAN managers and installers who need to do simple attenuation tests on their singlemode networks.

The **ZOOM 2C (Zeroed Output Optical Meter)** is an economical fiber optic power meter. It provides accurate testing of singlemode fiber cables. The 4-digit 7-segment LCD displays power readings with a resolution of 0.01dB. On-screen indicators display measurement units (dBm, dB, uW), as well as battery life. The ZOOM 2C comes configured with a 2.5mm universal connector for connection to ST or SC connectors, as well as any other fiber connector with a 2.5mm ferrule.

The **Laser OWL** is a 1310/1550nm NIST traceable singlemode light source. Its dual wavelength outputs are temperature-stabilized for accurate measurements. The Laser OWL has three connector options: ST, SC, or FC.

## Kit Contents

- Power Meter:** ZOOM 2C
- Light Source:** Laser OWL
- Accessories:** Product manuals  
9-volt batteries  
NIST certificate  
Carrying case  
Protective rubber boots



## Features

- Economical option for quick attenuation and loss testing singlemode networks
- Easy-to-read 4-digit 7-segment LCD display
- Store reference values for calibrated wavelengths
- Intuitive 2-button interface on both units
- On-screen wavelength, measurement units, and low battery indicator
- NIST traceable




ASSEMBLED IN USA

**N.I.S.T. Traceable**

Product manuals come in PDF format on CD. Adobe Acrobat Reader™ is required to view these documents.

Carrying cases and patch cables are available for an additional charge. Call 262-473-0643 for more information.



# ZOOM 2C / Laser OWL Test Kit

SKU: KIT-Z2C-L2xx (see connector options below)

Singlemode Fiber Test Kit

## Specifications

### ZOOM 2C Optical Power Meter

Detector	InGaAs
Calibrated Wavelengths	850nm, 1300, 1310nm, 1550nm
Measurement Range	+25 to -40 dBm
Accuracy <sup>1</sup>	±0.15 dB
Linearity <sup>1</sup>	±0.20 dB
Resolution	0.01 dBm
Battery Life	up to 250 hours
Operating Temperature	0 to 55°C
NIST Traceable	Yes
Battery Capacity Display	Yes
Connector	2.5mm Universal
Width	2.75"
Height	4.94"
Depth	1.28"
Weight	154g

1: Over range of +20 to -25 dBm

Conforms to the Harmonized European Standards EN 61326-1 and EN 61010-1.

### Laser OWL Singlemode Laser Source

Launch Method	FP Laser
Connector	ST, SC, or FC
Center Wavelength (1310nm)	1310 ±30nm
Center Wavelength (1550nm)	1550 ±30nm
Spectral Width (FWHM; 1310 / 1550 nm)	2 nm
Output Power	-10.0 dBm
Initial Accuracy	0.1 dB
Fiber Type	singlemode
Battery Life	25 hours
Battery Capacity Display	Yes
Operating Temperature	0 to 55° C
Storage Temperature	0 to 75° C
Width	2.75"
Height	4.94"
Depth	1.28"
Weight	154g

Conforms to the Harmonized European Standards EN 61326-1 and EN 61010-1.

