

Silicon WaveTester

Optical Power Meter

Features

- 1mm Silicon photodetector with 2.5mm universal adapter (ST, SC, and FC)
- Multimode ready
- Backlit graphic LCD display with intuitive user interface
- Simple 4-key operation
- Power measurements shown in dBm, dB, or microwatts
- Stores optical references for each wavelength to be used for optical loss testing
- Long battery life - over 250 hrs on one 9v battery
- Data storage for 100 points
- RS-232 interface for continuous data logging, report printing, or data downloading
- OWL Reporter software for downloading data and printing formatted fiber certification reports
- Power transformer port for continuous powering of the unit, or charging 9-volt NiCd or NiMH re-chargeable batteries
- Optional integrated Visual Fault Locator (VFL)



Applications

The Silicon WaveTester is a high accuracy, high resolution, microprocessor controlled, optical power meter. It has a 65dB dynamic range, and is NIST traceable at 850 making it ideal for multimode fiber network testing.

It has an attractive handheld case with a backlit, graphic, liquid crystal display, and 4-key keypad for easy operation. It is offered with a 2.5mm universal fiber connector, will operate for over 50 hours on a standard 9v battery, and has built-in auto shutdown.

The WaveTester will store reference values for each wavelength to be used for optical loss measurements, and can store up to 100 measured data points.

Stored data can be downloaded to our free OWL Reporter software to produce formatted certification reports.

Optionally, the battery charging port in the WaveTester can be replaced with a precision-coupled visual fault locator - optimized for fiber optics. Its high-intensity red laser allows for fiber identification up to 1.5 kilometers away.

It can also be used to check for faults within a few feet of its launch point. When the bright red light encounters a fault, the light is deflected into the jacket, producing a red glow at the point of the fault.

Key Specifications

Measurement range	+5 to -60dBm
Absolute accuracy ¹	+/- 0.15dB
NIST traceable calibrated wavelengths	850nm
Resolution	0.01dB
Precision ¹	+/- 0.05dB
Dimensions	4.94 x 2.75 x 1.28 in

Note 1: Over range of 0 to -45 dBm



MADE IN USA

N.I.S.T. Traceable

Product manuals come in PDF format on CD. Adobe Acrobat Reader™ is required to view these documents.



Carrying cases and patch cables are available for an additional charge. Call 262-473-0643 for more information.