

WaveSource VFL (WS-V)

Visual Fault Locator

Features

High-intensity visible laser allows for visible fault location of breaks and microbends in both single-mode and multimode fibers

Both Continuous Wave mode and Pulsed mode allow for easy fiber identification

ST, SC, and FC connector options available

Simple 4 button operation

CW Mode - 15 hours use on one 9v battery

Pulsed Mode - 120 hours use on one 9v battery

Low -battery indicator

Hand-held

Lightweight



SC connector shown here
Other connectors available



MADE IN USA

Product manuals come in PDF format on CD. Adobe Acrobat Reader™ is required to view these documents.



Carrying cases and patch cables are available for an additional charge. Call 262-473-0643 for more information.

Applications

The WaveSource VFL is a light-weight, hand-held tool used to quickly troubleshoot faults in the continuity of both single-mode and multimode fibers, especially at fiber launch points or in OTDR dead zones.

A high-intensity visible red laser beam is precision-coupled into a optical fiber; breaks and micro-bends in the fiber deflect the red light into the fiber jacket, producing a red glow at the point of the fault.

Additionally, it can be used as an end-to-end visual fiber identifier, which is useful for locating fibers terminated in poorly labeled or unlabeled fiber patch panels.

A simple 4-button interface is used to operate the WaveSource VFL.

Typical battery life in CW mode is 15 hours, and the short 12.5% duty cycle in pulsed mode extends the battery life to 120 hours of continuous use.

The WaveSource VFL has the option of ST, SC, or FC connectors.

Extreme caution must be exercised when operating this device. Lasers such as the ones in the WaveSource VFL produce intense beams of laser light that are harmful to the eye.

TO ENSURE YOUR SAFETY: NEVER LOOK INTO A LIGHT SOURCE OR THE END OF A FIBER THAT MAY BE ENERGIZED BY A SOURCE!

Exposure to such energy can cause serious retina damage, and prolonged exposure can cause blindness.


Key Specifications

Model Number	WS-V
Visual Range	up to 5 kilometers (3.1 miles)
Optical Output	-2 dBm (minimum) red laser
Optical Transmission	Continuous Wave or pulsed at 6 Hz w/12.5% duty cycle
Dimensions	4.94 x 2.75 x 1.28 in
Weight	6 ounces

Conforms to the Harmonized European Standards EN 61326-1 and EN 61010-1.



O.W.L. MANUFACTURER OF QUALITY OPTICAL FIBER TEST EQUIPMENT
OPTICAL WAVELENGTH LABORATORIES™



Optical Wavelength Laboratories (OWL)
N9623 West US Hwy 12
Whitewater, WI 53190
Phone (262)473-0643 Fax: (262)473-8737
<http://owl-inc.com>